



# Product data sheet

LIGHT LINEAR PT 2 BOLLARDS  
LI-10032-T3-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

### Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53.4 W	CRI	80
Total flux	6207 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	53.4 W

### Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53.4 W	CRI	80
Total flux	6207 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	53.4 W

### Mounting mode

Standing / Bollard

### Shape and measurements

Length: 22.83 in  
Width: 7.87 in  
Height: 39.37 in  
Weight: 14.9 kg

### Adjustability

Fixed

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 106.8 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C