


# Product data sheet

POWERSVISION 2 SURFACE HIGH BAY LUMINAIRES  
PW29-GP080-T4-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Extruded aluminium pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

### Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	74.1 W	CRI	80
Total flux	9355 lm	LOR	100%
Luminous efficacy	126 lm/W	Total power	74.1 W

### Mounting mode

Ceiling mounted, Wall mounted

### Shape and measurements

Length: 18.90 in  
Width: 11.22 in  
Height: 11.81 in  
Weight: 11 kg

### Adjustability

Fixed

### Design

Color of housing: Black, White, Silver gray

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 74.1 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

### Protection

IP: 66  
IK: 07  
Surface temperature: 40°C