


Product data sheet

FLAT POLYMERO
672056.002.5.89
RZB




IP
40

IK
03

Item Number: 672056.002.5.89 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Mounting support body metal powder-coated, cover fixed by pressure lock, cover plastic (PMMA), opal, with AC Control monitoring module for Luxfair central battery units. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 360, , H 100mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: AC-Control Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1450lm System power: 15W Beam Angle: 116° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 19,1 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	14 W	CRI	80
Total flux	1450 lm	LOR	100%
Luminous efficacy	104 lm/W	ULOR	12%
		Total power	14 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.94 in
Diameter: 14.17 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 40
IK: 03