


# Product data sheet

NEUTRON 1  
07.9201/QR-CBC35/20W/10°38°  
FLOS




Adjustable recessed luminaire for ceilings or in ground applications, for LEDs or 12 volt halogen QR-CBC35 lamps. Die-cast aluminum recessed housing, high corrosion-resistance.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 20 W    | Socket      | Gu4    |
| Lamp flux          | 247 lm  | LOR         | 100%   |
| Luminous efficacy  | 12 lm/W | Total flux  | 247 lm |
| CCT                | 3000 K  | Total power | 20 W   |
| CRI                | 99      |             |        |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 20 W    | Socket      | Gu4    |
| Lamp flux          | 247 lm  | LOR         | 100%   |
| Luminous efficacy  | 12 lm/W | Total flux  | 247 lm |
| CCT                | 3000 K  | Total power | 20 W   |
| CRI                | 99      |             |        |

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 4.72 in  
Diameter: 4.92 in

## Adjustability

Free

## Electric

System power: 20 W  
Appliance Class: I

## Protection

IP: 66