


Product data sheet

BTECSE L22 LE3
BTEC SECURE EMERGENCY
DEXTRA




Btec Secure UGR Downlighter - IP65, IK10, Recessed downlighter with spun aluminium housing, spring steel retaining clips and high transmission polycarbonate diffuser. When installed with anti-pick mastic to seal the luminaire to the mounting surface the BTEC Secure complies with ligature resistant requirements of the Department of Health Environmental Design Guide, Adult Medium Secure Services. Lighting control options: S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) RLI - Reacta-Link, Wireless Enabled Luminaire RC - Reacta-Control, Wireless Enabled Luminaire Emergency options: LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest

Light output 1 (integrated, emergency)



Lamp type		CCT	4000 K
Nominal lamp power	4 W	CRI	80
Total flux	377 lm	LOR	100%
Luminous efficacy	94 lm/W	Total power	4 W

Light output 2 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	15.4 W	CRI	80
Total flux	1633 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	15.4 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.80 in
Diameter: 8.74 in

Adjustability

Fixed

Electric

System power: 19.4 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 65

IK: 10

Resistant to impact of balls

Designation labels: CE