# Product data sheet


SPIKE BLACK W/ OUTLET 880LM 3000K RA>80 TRAILING EDGE DIMMING

7021986149111



Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct Light technic LED 10W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP44 IK08 Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Outdoor Screwless terminal block

#### Light output 1



# 1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI

10 W 880 lm 88 lm/W 3000 K 80

LOR
Total flux
Total power

100%
880 lm
10 W

## Mounting mode

Wall mounted

#### Shape and measurements

Length: 6.53 in Width: 6.01 in Height: 6.69 in

#### Adjustability

Fixed

#### Design

Color of housing: Black

### Electric

System power: 10 W Appliance Class: I

#### Protection

IP: 44 IK: 08