

Product data sheet


ALBRECHT /1 R U LED
5.706.9433.05-2LK1
LEIPZIGER LEUCHTEN



IP
65

recom. pole height: 3.00m – 5.00m light standards: low and medium lighting requirements lamp: incl. 1 or 2 LLM LED modules 1 , incl. 1 U LED module 2 or incl. 1 FLS LED module 4 , easy to replace; optionally: spot FRIEDER X LED 12 colour temperature: 3.000K warm white or 4.000K neutral white LED gear: electronic driver up to 100.000 hours; CLO mode LED life expectancy: up to 50.000 hours/ L100; U LED: up to 100.000 hours/ L90; spot: 50.000 hours/ L70 light control: at extra cost: dimming; power reduction; U LED: external change of dim settings optical system: LLM LED: reflector system; U LED: louvre system with anti-glare tube; U LED pearl structured, satined: without louvre, diffuse; FLS LED, spot: by lens technology light distribution: LLM LED: extreme wide beam; U LED: symmetrical or asymmetrical; FLS LED: S oval wide beam, A asymmetrical wide beam, P symmetrical light distribution; spot: 30°; 40°, 60° on request luminaire head: incl. canopy with top and 6 decor elements with hinge; made of corrosion-resistant cast aluminium; powder coated; optionally: spot with magnetic ball joint for individual settings bracket: optionally: wall bracket WA I, WA VI: made of hot dip galvanised steel; WA VII: made of cast aluminium; powder coated colour: RAL or DB glazing: PMMA RESIST, clear, pearl structured or satined, high-impact resistant wiring: luminaire head completely wired, incl. cable installation: to be screwed on heritage columns or on wall brackets resp. with adapter AD 76 for top entry ø 76mm or pedestal accessory: column, wall bracket, adapter AD76, spot FRIEDER X, pole accessories, wall fixing materials – to be ordered separately application areas: historic center, pedestrian zones, parkways, schools, hotels, factory premises, residential and local distribution roads, squares, car parks

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1849 lm	ULOR	26%
Luminous efficacy	103 lm/W	Total flux	1849 lm
CCT	4000 K	Total power	18 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Height: 38.78 in

Diameter: 24.80 in

Adjustability

Height adjustable

Electric

System power: 18 W

Protection

IP: 65