


Product data sheet

SIGNALLEUCHTEN
50605.007
RZB




IP
43

IK
04

Series: Signalleuchten Type of Protection: IP 43 Protection Class: II Voltage: - 250 / 0 - 60 Hz Base: plastic, grey. Two cable inlets. Cover: plastic, coloured, glossy. Screw mounting. RZB luminaires for construction sites are labelled as follows: Signal luminaire DIN 67527-C-2-3: When mounted to a wall the lampholder must be pointing upwards (suspended lamp). Available Colours: yellow Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 195, B 132, H 115 Lamp: 1 x E27 max. 60 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK04 (0,50 Joule) Beam Angle: 90°/90°/90°/61° Unified Glare Ratio: 23,1 EEC: A++ - E

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	8 W	Socket	E27
Lamp flux	400 lm	LOR	86%
Luminous efficacy	43 lm/W	ULOR	21%
CCT	2700 K	Total flux	346 lm
CRI	80	Total power	8 W

Mounting mode

Wall mounted

Shape and measurements

Length: 5.20 in
Width: 7.68 in
Height: 4.13 in

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 43
IK: 04