


Product data sheet

CANNON 280
2020-6-4-906-XX
UNILAMP



CANNON By its very name Cannon has a robust construction and is suitable in applications that require high lighting levels from medium to long distance. A wide range of mounting accessories including ground mount base, pole top mount, and wall/pole mount arm is available. This luminaire utilizes a high power COB LED from Citizen Japan. CANNON is available in 2 sizes in mid-narrow, mid-wide and very wide beam angle in 2700K, 3000K and 4000K. The pure aluminium reflector used is designed by high-end lighting engineering software. The calibrated and ease of installation allows the lighting designer to have confidence that the light distribution will be exact on any surface. CANNON is suitable to light up medium size to large size objects or areas such as billboards, building facades, public parks, pedestrian, statues and public landmarks. Specification • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium reflector. • Adjustable optic. • M20 cable gland. • Installation work has to be carried on according to the enclosed installation manual.

Light output 1



1 x LED			
Nominal lamp power	52 W	LOR	86%
Lamp flux	8980 lm	Total flux	7733 lm
Luminous efficacy	173 lm/W	Total power	60 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 3.16 in

Width: 10.24 in

Height: 11.62 in

Adjustability

Free

Electric

System power: 60 W

Appliance Class: I

Protection

IP: 66

IK: 09