



Product data sheet

LESS IS MORE 50
312166.000.1.76
RZB



Series: Less is more 50 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: extruded anodised aluminium profile. End caps made of plastic, light-deflecting segments made of plastic (ABS) aluminium vapour-plated, highly polished, symmetrical beam, with diffuser made of plastic (PC) opal. Converter included. Lamp (LED) included. Available Colours: anodised aluminium Type of Installation: Ceiling mounting Dimensions: L 1140, B 53, H 65 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3800lm System power: 37W Beam Angle: 60°/58° Number of fittings B10A: 8 Number of fittings B16A: 13 Inrush current: 53A Unified Glare Ratio: 16,2 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 37 W | CRI | 80 |
| Total flux | 3800 lm | LOR | 100% |
| Luminous efficacy | 103 lm/W | Total power | 37 W |

Mounting mode

Ceiling mounted

Electric

System power: 37 W

Shape and measurements

Length: 2.09 in
Width: 44.88 in
Height: 2.56 in

Protection

IP: 20
IK: 03

Adjustability

Fixed