# Product data sheet

ALDO 1 FLOODLINGHTS AND COLUMN PROJECTORS ALD-30011-EW-W40

LIGMAN










- Lamp LED - Colour 3000K and 4000K - Powder coated aluminium alloy housing - Adjustable stainless steel bracket - Two cable entries for through wiring - Bright and consistent distribution, with seamless treatment with continuous mounting - Constant voltage (CV) 24V - Remote driver is not included - DC24V input, DMX512 address with constant current control for RGBW products

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	11.7 W	CRI	80
Total flux	762 lm	LOR	100%
Luminous efficacy	65 lm/W	Total power	11.7 W

#### Mounting mode

Standing / Bollard, Ceiling mounted

## Shape and measurements

Length: 39.37 in Width: 0.63 in Height: 1.57 in Weight: 0.64 kg

## Adjustability

Fixed

#### Design

Color of housing: Black, White, Silver gray

#### Glare protection

Glare protection: UGR < 19

#### Electric

System power: 11.7 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: III

## Protection

IP: 65 IK: 08

Surface temperature: 40°C Designation labels: CE