

Product data sheet

AL600 LED, 16W LED / 3200K - VERY WIDE


5742580676

LOUIS POULSEN




AL 600 Design : Mads Odgård Concept : The fixture has either a wide or very wide beam width. The two lightdistributions expand the flexibility in optimizing the lighting in narrow surroundings like tunnels and arcades. The design is low and sturdy. Finish : Aluminium coloured with textured surface, powder coated. Material : Housing: Die cast aluminium. Diffuser: Polycarbonate. Mounting : Looping: Approved. Integral ballast. Installation cabel: 8-13mm. (not enclosed). Class : Ingress protection IP65. Electric shock protection I w. ground. Vandal Proof II. IK10. Weight : Max. 3 kg.

Light output 1



1 x Fluorescent lamp ring shaped

Nominal lamp power	40 W	LOR	100%
Lamp flux	3300 lm	Total flux	3299 lm
Luminous efficacy	73 lm/W	Total power	45 W
CCT	3000 K		
CRI	85		



1 x LED

Nominal lamp power	17 W	LOR	100%
Lamp flux	1045 lm	Total flux	1045 lm
Luminous efficacy	61 lm/W	Total power	17 W
CCT	3000 K		
CRI	85		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.62 in

Width: 4.06 in

Height: 1.57 in

Adjustability

Fixed

Electric

System power: 17-45 W

Appliance Class: II

Protection

IP: 65