


Product data sheet

L-COLUMN INTERLLIGENT LIGHT COLUMN
LCO-20062-M-W40
LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear installed in the pole

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	21.1 W	CRI	80
Total flux	1731 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	21.1 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	21.1 W	CRI	80
Total flux	1731 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	21.1 W

Mounting mode

Wall mounted, Pole integrated

Shape and measurements

Height: 30.91 in
Diameter: 8.27 in
Weight: 15.8 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 42.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 04

Surface temperature: 40°C