

Product data sheet


PETRA PI (BOLLARD)
9.883.5557.30
LEIPZIGER LEUCHTEN



IP
55

Decorative luminaire for lanes, driveways, terraces, gardens and for night illumination and hazardous areas. Light exit on one side. - Impact-resistant opal polycarbonate attachment,UV-stabilized - Luminary body/upright tube of special steel painted in any RAL or DB colour without surcharge, or special steel, ground and passivated - All electrical components accommodated on a block -Crown detachable for easy maintenance/lamp change - Upright tube without pole door, incl. adapter jack - Upright tube with pole door, incl. cable joint box for cable 5 x 16 mm2 - incl.....Dulux L24W-31-830 SP Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

Light output 1



| | | | |
|--------------------|---------|-------------|--------|
| 1 x DULUX L-SP | | | |
| Nominal lamp power | 24 W | LOR | 36% |
| Lamp flux | 1800 lm | ULOR | 19% |
| Luminous efficacy | 24 lm/W | Total flux | 644 lm |
| CCT | 2899 K | Total power | 27 W |
| CRI | 90 | | |

Mounting mode

Standing / Bollard

Shape and measurements

Height: 44.49 in
Diameter: 3.94 in

Electric

System power: 27 W

Protection

IP: 55