


Product data sheet

LOWIEZE HIGH IP54 2X LED 3000K FLOOD GI BLACK STRUCTURE
12672408
MODULAR




Lowie and Lowieze are perfect examples of form blending with function. The basic shape here is the cylinder. The two bulb housings – which are also cylindershaped – on either side of the body can rotate fully on their axis and thus be used as an uplighter or a downlighter. What’s more, the two bulb housings can be moved individually, meaning you can use one fixture to simultaneously light two places. Lowie and Lowieze also come in a one-lamp version, with only one bulb housing on the cylinder.

Light output 1



1 x LED			
Nominal lamp power	5 W	LOR	80%
Lamp flux	261 lm	Total flux	208 lm
Luminous efficacy	42 lm/W	Total power	5 W
CCT	3000 K		
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	5 W	LOR	80%
Lamp flux	261 lm	Total flux	208 lm
Luminous efficacy	42 lm/W	Total power	5 W
CCT	3000 K		
CRI	90		

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 2.76 in

Width: 2.76 in

Height: 23.82 in

Adjustability

Tiltable

Electric

System power: 10 W

Appliance Class: I

Protection

IP: 54

IK: 01