


Product data sheet

FLOODLIGHT 48LED 108W T4000 S60-OPT. AL
67300000400401-67300001400401
TELEVES



Televes Floodlight is a range of extremely efficient symmetric or asymmetric floodlights that can be used to illuminate large areas. Designed around the latest LED technology. Integrated controls are available as an option, enabling additional energy savings. Model with 48 LEDs 4000K IRC>70 700mA. Maximum input power 100W. IP67. IK10. Class II. Light distribution Narrow 60°. System efficacy: Up to 150lm/W. Multi-array optics. Lifetime: L80F10 Up to >100Khrs Ta=25°C. Free adjustable bracket. Aerodynamic design. Body in extruded 6063 T5 aluminum. Excellent thermal management. Vent integrated to prevent moisture and balance atmosphere pressure. Standard finish in RAL9006. AVAILABLE DISTRIBUTIONS • PZ - Asymmetric • Wide Flood 90° • Narrow Flood 60° • Flood 30°

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	108 W	CRI	75
Total flux	15750 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	108 W

Mounting mode

Pole integrated

Shape and measurements

Length: 13.58 in
Width: 10.04 in
Height: 3.54 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 108 W
Appliance Class: II

Protection

IP: 67
IK: 10