
Product data sheet

LESS IS MORE 27 312177.002.1

RZB








Series: LESS IS MORE 27 Recessed ceiling and wall luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. High polish aluminium micro grid. Perfect for office areas (UGR < 19) and environments with computer screens in accordance with EN 12464-1. Suitable for recessed ceiling mounting, wall (recessed). External driver with connecting cable. Colour: traffic white, matt (RAL 9016) Length: 1014 mm Width: 38 mm Height: 2 mm Cut-out length: 1006 mm Cut-out width: 30 mm Recess height: 45-60 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 82 System power: 25 W Rated luminous flux: 2350 lm Luminous efficiency: 94 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25 W	CRI	80
Total flux	2350 lm	LOR	100%
Luminous efficacy	94 lm/W	Total power	25 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 1.50 in Width: 39.92 in Height: 0.08 in

Adjustability

Fixed

Electric

System power: 25 W

Protection

IP: 20