

# Product data sheet


INDIGO LED HB-D 4000K DALI CLO  
24653-454  
FAGERHULT



IP  
20

Installation Recessed mounting in suspended ceilings. Unventilated or ventilated ceilings. Two optional designs: VTB – for suspended ceilings with visible T-bars (25 or 15 mm). HB – for suspended ceilings with concealed T-bars and symmetrical ceiling tiles. Four suspension fittings included. For fixed roofs (plaster etc.) suspension fittings for an HB body can be ordered separately. Do not cover with insulation. For detailed information, see the installation instructions. Connection Connected to 2.5 mm<sup>2</sup> 3-way terminal block with the possibility of through-wiring. With additional number for 5-way terminal block dimming. Can also be supplied with mains cable and earthed plug or chassis mounted snap-in connector. Designed by Luminaire body of white enamelled (RAL 9016) sheet steel. Louvre Diffuser in Opal acrylic. Miscellaneous The luminaire has a switch for high/ low flow easily accessible at the rear of the luminaire. Always delivered set at high flow.

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 34 W     | CRI         | 80     |
| Total flux         | 3400 lm  | LOR         | 100%   |
| Luminous efficacy  | 100 lm/W | Total power | 34 W   |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.58 in  
Width: 23.58 in  
Height: 5.98 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 34 W

## Protection

IP: 20