

Product data sheet

FLAT POLYMERO KREIS
311926.002.3.76
RZB




IP
40

IK
03

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic (PMMA). Diffuser fastening: push lock. Available Colours: white Type of Installation: Pendant Dimensions: D 360, H 87 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1550lm System power: 14W Beam Angle: 126° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 19,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14 W	CRI	80
Total flux	1550 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	17%
		Total power	14 W

Mounting mode

Pendant

Shape and measurements

Height: 3.35 in
Diameter: 14.17 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 40
IK: 03