


Product data sheet

BASIC MINI LED 3000K 12W
5742586874
LOUIS POULSEN



Basic Mini Design: Louis Poulsen A/S Concept: The mini downlight has a 100% downward directed light distribution. With its matt reflector diffuses the light softly creating a comfortable vertical illumination. The white ring gives a subtler transition to the ceiling surface. Finish: White, powder coated. Material: Rings: Punched steel. Mounting: Ceiling thickness: 5-32mm. Ceiling cut-out: Ø 105mm. Looping: Not approved. Driver hardwired to housing. For more information please look at www.louispoulsen.com. Weight: Max. 0.5kg. Class: Ingress protection IP20. Electric shock protection III low voltage. Info notes: Supplied with light source. For LED replacement kits please do contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website www.louispoulsen.com

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	90
Total flux	792 lm	LOR	99%
Luminous efficacy	53 lm/W	Total power	15 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.50 in
Diameter: 4.88 in

Adjustability

Fixed

Electric

System power: 15 W
Appliance Class: III

Protection

IP: 20