


# Product data sheet

MINIFRANCO LED  
1628013  
FLOS



Outdoor luminaire for installation on wall or on pole. Configuration: die-cast aluminium structure. EN AB-47100 (low copper content) Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Pure aluminium optics, tempered extra-clear glass diffuser, silicone gaskets.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	1688 lm	LOR	100%
Luminous efficacy	70 lm/W	Total power	24 W

## Mounting mode

Wall mounted, Pole top mounted

## Shape and measurements

Length: 6.89 in  
Width: 4.17 in  
Height: 9.65 in

## Adjustability

Tiltable

## Electric

System power: 24 W  
Appliance Class: I

## Protection

IP: 65  
IK: 07