


Product data sheet

SIRIUS 600 - CC WALL WASHER
8031-C-2-688-XX
UNILAMP




A brand new linear light family features various mounting application types including In-ground walk over, wall mounted, wall recessed, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1




1 x LED			
Nominal lamp power	4.3 W	LOR	99%
Lamp flux	518 lm	ULOR	99%
Luminous efficacy	120 lm/W	Total flux	514 lm
CCT	4000 K	Total power	4.3 W
CRI	85		

Light output 2




1 x LED			
Nominal lamp power	4.5 W	LOR	99%
Lamp flux	136 lm	ULOR	99%
Luminous efficacy	30 lm/W	Total flux	135 lm
CCT	0 K	Total power	4.5 W
CRI	-50		

Light output 3



1 x LED			
Nominal lamp power	4.1 W	LOR	99%
Lamp flux	467 lm	ULOR	99%
Luminous efficacy	114 lm/W	Total flux	464 lm
CCT	8000 K	Total power	4.1 W
CRI	-23		

Light output 4



1 x LED			
Nominal lamp power	3.4 W	LOR	99%
Lamp flux	192 lm	ULOR	99%
Luminous efficacy	56 lm/W	Total flux	190 lm
CCT	0 K	Total power	3.4 W
CRI	-36		

Mounting mode

Wall mounted

Shape and measurements

Length: 2.16 in
Width: 15.88 in
Height: 1.57 in

Adjustability

Free

Electric

System power: 16.3 W
Appliance Class: III

Protection

IP: 67
IK: 07