Product data sheet

VOLKMAR III (WALL FITTING) 9.840.0087.00

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| 1 x High pressure sodium vapour lamp | | |
|--------------------------------------|----------|--|
| Nominal lamp power | 100 W | |
| Lamp flux | 10400 lm | |
| Luminous efficacy | 49 lm/W | |
| CCT | 2000 K | |
| CRI | 25 | |

| LOR | 55% |
|-------------|---------|
| ULOR | 15% |
| Total flux | 5680 lm |
| Total power | 115 W |
| | |



1 x High pressure sodium vapour lamp

| Nominal lamp power | 70 W | LOR | 55% |
|--------------------|---------|-------------|---------|
| Lamp flux | 5600 lm | ULOR | 15% |
| Luminous efficacy | 37 lm/W | Total flux | 3059 lm |
| CCT | 2000 K | Total power | 83 W |
| CRI | 25 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

System power: 83-115 W

Protection

IP: 55