



Product data sheet

NOTUS 1 CROSS LOW UGR 2579MM
840
BRIGHT SPECIAL LIGHTING




Housing :Extruded aluminium Diffuser :Extruded PMMA | Cross Control Gear :Built-in electronic driver UGR :≤19 with special covers
Transmittance :80% IP :40 IK :04

Light output 1



1 x LED			
Nominal lamp power	69.7 W	LOR	100%
Lamp flux	10697 lm	Total flux	10697 lm
Luminous efficacy	153 lm/W	Total power	69.7 W
CCT	3783 K		
CRI	84		



1 x LED			
Nominal lamp power	50.9 W	LOR	100%
Lamp flux	7253 lm	Total flux	7253 lm
Luminous efficacy	142 lm/W	Total power	50.9 W
CCT	3783 K		
CRI	84		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 101.54 in
Width: 3.15 in
Height: 3.50 in

Adjustability

Free

Glare protection

Glare protection: UGR < 19

Electric

System power: 50.9-69.7 W
Ballast: ECG
Controller: Dimmable 0..10V, Dimmable 1..10V, DALI
Color adjustable
Appliance Class: I

Protection

IP: 40
IK: 04