
Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, FULLY RECESSED ADJUSTABLE SPOTLIGHT

AF2103008-33-30_(ALPHA-MAX)


SCHMITZ | WILA





alphabet focus LED 3000 K Recessed Luminaire, Light distribution direct Fully Recessed Adjustable Spotlight Product: AF2103008-33-30 Operating technology: independent driver required Light Technique highly precise lens technology (PLT) for beam angles, with focus unit for stepless fine adjustment Light module 361° rotatable, with integrated rotation stop tilt range from 0-30° variable beam angles 24° - 40° CRI > 90 constant colour temperature 3000 K lifetime 50.000 h (L70) Aluminium reflector (Al99.98), high- polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling cover frame white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 36 W Colour Rendering Index: 90 Colour Temperature: 3000 K Luminaire Luminous Flux: 830 Llm - 1590 Llm System Efficiency: 41 Llm/W Half-peak Divergence a: 24° - 40° Number Luminaires LZ: 0.14 -0.07 Connector: Screw Connector, 3 x 1.5 mm2 Reflector Size: Q10 Length: 127 mm Width: 127 mm Cut-out length: 120 mm Cut-out width: 120 mm Overhang OH: 115 mm Installation Depth RD: 200 mm Total Weight: 1.1 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF2103008-33-30_(Alpha-MAX)

Light output 1



CCT

CRI

1 x General service incandescent lampNominal lamp power39 WLamp flux1590 lmLuminous efficacy41 lm/W

3000 K

90

OR	100%
otal flux	1590 lm
otal power	39 W

Mounting mode	Electric
Ceiling recessed	System power: 39 W
Shape and measurements	Appliance Class: II
Length: 5.00 in	Protection
Width: 5.00 in	IP: 20
Height: 7.87 in	
Adjustability	
Fixed	

Design

Color of housing: White