# Product data sheet

ASY WINK 115 LED GE 3000K SPOT BLACK STRUC 13071132

MODULAR









The new Modular recessed spot Not only Wink's technical ingenuity may best be called remarkable, but also its sense of humor. As its name recalls, Wink is a recessed spotlight that likes to wink at you. The straightforward approach, in combination with refined lines and detailed workmanship, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. Wink is perfect for any residential or hospitality project, thanks to its symmetric or asymmetric lighting experience. Its identical design allows you to combine both versions, in order to create different lighting effects in the same room.

#### Light output 1




| IXLED              |         |
|--------------------|---------|
| Nominal lamp power | 11 V    |
| Lamp flux          | 984 ln  |
| Luminous efficacy  | 55 lm/V |
| CCT                | 3000 H  |
| CRI                | 90      |
|                    |         |

| LED              |         |             |        |
|------------------|---------|-------------|--------|
| minal lamp power | 11 W    | LOR         | 80%    |
| mp flux          | 984 lm  | Total flux  | 784 lm |
| minous efficacy  | 55 lm/W | Total power | 14.2 W |
| Т                | 3000 K  |             |        |
| I                | 90      |             |        |
|                  |         |             |        |
|                  |         |             |        |



| 1 x LED            |         |             |  |
|--------------------|---------|-------------|--|
| Nominal lamp power | 23.4 W  | LOR         |  |
| Lamp flux          | 1627 lm | Total flux  |  |
| Luminous efficacy  | 49 lm/W | Total power |  |
| CCT                | 3000 K  |             |  |
| CRI                | 90      |             |  |



| 1 x LED            |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 16.2 W  | LOR         | 80%     |
| Lamp flux          | 1297 lm | Total flux  | 1034 lm |
| Luminous efficacy  | 53 lm/W | Total power | 19.5 W  |
| CCT                | 3000 K  |             |         |
| CRI                | 90      |             |         |
|                    |         |             |         |

#### Mounting mode

Ceiling recessed

80% 1297 lm 26.7 W

## Shape and measurements

Length: 4.53 in Width: 4.53 in Height: 3.94 in Weight: 0.87 kg

## Adjustability

Fixed

#### Electric

System power: 14.2-26.7 W

Appliance Class: III

## Protection

IP: 54