


Product data sheet

LOUI 50
925362.0045.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Colour: silver, matt (approx. RAL9006) Length: 1401mm Width: 71mm Height: 1.5mm Cut-out length: 1408mm Cut-out width: 60mm Recess height: 100mm Luminaire: recess height: 75mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 35W Rated luminous flux: 4200lm Luminous efficiency: 120lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	4200 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	35 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 55.16 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 20
IK: 03