



Product data sheet

LIGHTSOFT 2 BOLLARDS
LH-10593-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° > 55,400 - Life time L80B10 Ta 50° > 55,400 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, UV-stabilised, polycarbonate diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	14.3 W	CRI	80
Total flux	347 lm	LOR	100%
Luminous efficacy	24 lm/W	ULOR	14%
		Total power	14.3 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 4.02 in
Width: 4.02 in
Height: 23.62 in
Weight: 3.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 14.3 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C