


Product data sheet

FLAT POLYMERO
672059.002.5.19
RZB




IP
40

IK
03

Item Number: 672059.002.5.19 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Mounting support body metal powder-coated, cover fixed by pressure lock, cover plastic (PMMA), opal, single battery system as standard with automatic self-test, status display on the luminaire and with movement detector. Parameters of the movement sensor at ceiling height of max. 4 m or wall mounting of max. 2.7 m: - HF detector 5.8 GHz ISM frequency band - sensitivity/range 1-10 m, diameter (20-100%) adjustable - time control approx. 10 seconds to 30 minutes, adjustable - detection range 120° - transmission power <5.0 mW - brightness levels: daylight / 300Lux / 150Lux dusk / darkness / teach mode - switching capacity 800W (incandescent lamp), 500 W (fluorescent lamp, LED) - only suitable for outdoor use to a limited extent on account of sensitive reaction to all movements. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, , H 120mm Lamp: LED + LED 1.5 W Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: automatic self-test Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) System power: 22W Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2100 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	10%
		Total power	19 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.72 in

Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 19 W

Protection

IP: 40

IK: 03