

Product data sheet

FLAT POLYMERO KREIS
311613.002.3.76
RZB




IP
40

IK
03

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 110 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 98 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2250lm System power: 36W Beam Angle: 124° Number of fittings B10A: 4 Number of fittings B16A: 7 Number of fittings C10A: 8 Number of fittings C16A: 12 Inrush current: 40A Unified Glare Ratio: 18,5 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	2250 lm	LOR	100%
Luminous efficacy	62 lm/W	ULOR	17%
		Total power	36 W

Mounting mode

Ceiling mounted

Electric

System power: 36 W

Shape and measurements

Height: 3.86 in
Diameter: 20.28 in

Protection

IP: 40
IK: 03

Adjustability

Fixed