

Product data sheet

FLAT POLYMERO
311593.002.2.76
RZB




IP
40

IK
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 150 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 3500lm System power: 35W Beam Angle: 115° Number of fittings B10A: 10 Number of fittings B16A: 17 Number of fittings C10A: 16 Number of fittings C16A: 26 Inrush current: 49A Unified Glare Ratio: 20,2 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	3500 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	8%
		Total power	35 W

Mounting mode

Ceiling mounted

Electric

System power: 35 W

Shape and measurements

Height: 5.91 in
Diameter: 20.28 in

Protection

IP: 40
IK: 10

Adjustability

Fixed