

Product data sheet

VOLKMAR II (3-ARMED)

9.870.0209.05


LEIPZIGER LEUCHTEN



IP
55

For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection - Available in any RAL - or DB -colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1




1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	42 lm/W
CCT	3400 K
CRI	54

LOR	85%
ULOR	28%
Total flux	5755 lm
Total power	137 W

Light output 2




1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	42 lm/W
CCT	3400 K
CRI	54

LOR	85%
ULOR	28%
Total flux	5755 lm
Total power	137 W

Light output 3



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	42 lm/W
CCT	3400 K
CRI	54

LOR	85%
ULOR	28%
Total flux	5755 lm
Total power	137 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in

Diameter: 16.14 in

Electric

System power: 411 W

Protection

IP: 55