


Product data sheet

TANGO 37 CYLINDRICAL POST TOP LUMINAIRES
TA-20021-W-W40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Extruded aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass lens - Maximum wind load resistance is 140 km/h

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	38.5 W	CRI	80
Total flux	3883 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	38.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	38.5 W	CRI	80
Total flux	3883 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	38.5 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 25.59 in
Diameter: 7.32 in
Weight: 23.5 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 77 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C