


Product data sheet

RAX SURFACE 200 WHITE 2260LM 3000K RA>80 DALI PUSH DIM
5703821164245
SG ARMATUREN



Rax 200 Surface is designed for applications with solid ceilings and will reduce lighting costs without compromising the visual quality of indoor environments. The unique reflector design combined with the latest LED technology ensures high efficiency. Light distribution Direct Light technic LED 19W 3000K Ra>80 SDCM 2 L90/B10 >50,000 hrs at Ta=25°C Control/Dimming DALI Push Dim Protection Class I IP20 Energy and approvals A++ CE Materials and finish Housing: Spun aluminium Colour: White Optics: Aluminium Mounting/Connection Surface, Indoor Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light output 1



1 x LED			
Nominal lamp power	19 W	LOR	100%
Lamp flux	2260 lm	Total flux	2261 lm
Luminous efficacy	119 lm/W	Total power	19 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 8.78 in
Width: 8.78 in
Height: 9.96 in

Adjustability

Fixed

Electric

System power: 19 W
Appliance Class: I

Protection

IP: 20