


# Product data sheet

FLAT POLYMERO  
672386.002.04  
RZB




IP  
40

IK  
03

Item Number: 672386.002.04 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Mounting support body metal powder-coated, cover fixed by pressure lock, cover plastic (PMMA), opal, single battery system, automatic self-test with bus connection for feedback to the RZB Multidigit, RZB MWEBplus and S63 monitoring systems. Additional status display on the luminaire. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, , H 150mm Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: MultiDigit Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2600lm System power: 27W Beam Angle: 117° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 19,1 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.4 W	CRI	80
Total flux	2600 lm	LOR	100%
Luminous efficacy	95 lm/W	ULOR	12%
		Total power	27.4 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 5.91 in  
Diameter: 20.28 in

## Adjustability

Fixed

## Electric

System power: 27.4 W

## Protection

IP: 40  
IK: 03