


# Product data sheet

LP CIRCLE SEMI RECESSED Ø260 WHITE LED 4000K 13W  
5742587828  
LOUIS POULSEN



LP Circle Semi Recessed Design: Mikkel Beedholm/KHR arkitekter Concept: The fixture emits diffuse light via a high-efficiency acrylic diffuser. The diffuser, which is encircled by a voluminous coloured or white ring, is hidden when viewed from low angles. Angling the inner side of the ring 5° creates a comfortable and decorative graduation of the light from the diffuser. With two diameters and four different installation options, the lights series can be used for a wide range of applications. Finish: White, Black, Pale Petroleum or Yellow. Powder coated. Material: Reflector: Extruded aluminium. Diffuser: Acrylic, frosted. Installation lock: Polyamide. Mounting: Ceiling thickness: 1–40 mm. Driver is a separate unit (supplied with fixture). Cut-out dimensions: Ø 260: Ø 248mm, Ø 450: Ø 438mm. Looping: Approved, max 5x1.5mm<sup>2</sup>. Weight: Min: 2.4 kg Max: 5.0 kg Class: Ingress protection IP20. Electric shock protection I.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	90
Total flux	1377 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 10.47 in  
Width: 10.47 in  
Height: 4.06 in

## Adjustability

Fixed

## Electric

System power: 13 W

## Protection

IP: 20