# Product data sheet


MRZ-4 MULTI-HEAD RECESSED INTEGRAL LED MRZ-1-REC-X-2-L27-80-WFL-UNV-X-STD COOPER LIGHTING





Family of 1, 2, 3, or 4-head fixtures, Lumen packages from 250 to 1700+ per head in 80+ or 97+ CRI, +110 LPW, 25°, 40°, 55° optics; each head has 45° tilt with 365° degree rotation, Black housing & white trim/white housing & trim/black housing & trim, IC-rated fixtures with flanged and mud-in trims, 0-10V std dimming. Optional: 0.1%, 1%, Lutron, and Fifth Light DALI, LumaWatt Pro and WaveLinx connected lighting platforms available, Linear spread lens, soft focus lens, hex louver, and snoot option, Chicago plenum and emergency battery options

### Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	8.85 W	CRI	80
Total flux	838 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	8.85 W

# Mounting mode

Ceiling recessed

## Shape and measurements

Height: 0.39 in Diameter: 2.00 in

## Adjustability

Fixed

#### Electric

System power: 8.85 W

### Protection

IP: 47