


Product data sheet

PURE 1
09.1600/QR-CBC/50W/10°24°36°60°
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1182 lm	LOR	100%
Luminous efficacy	24 lm/W	Total flux	1182 lm
CCT	3000 K	Total power	50 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	995 lm	LOR	100%
Luminous efficacy	20 lm/W	ULOR	5%
CCT	3000 K	Total flux	995 lm
CRI	100	Total power	50 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1012 lm	LOR	100%
Luminous efficacy	20 lm/W	ULOR	4%
CCT	3000 K	Total flux	1010 lm
CRI	100	Total power	50 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1025 lm	LOR	100%
Luminous efficacy	20 lm/W	ULOR	6%
CCT	3000 K	Total flux	1025 lm
CRI	100	Total power	50 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in

Width: 3.94 in

Height: 5.51 in

Adjustability

Rotatable, Tilttable

Electric

System power: 50 W

Appliance Class: II

Protection

IP: 20