



Product data sheet

ALEA SPOT
641319.004.1.76
RZB



Series: Alea Spot Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Pole: aluminium. Cover: plastic sphere, opal, satin finish. "Triple lamp; mains connection through pole to terminal in" "pole top; base plate: D 300. 4 mounting holes: D 10; pitch" circle for holes: D 230. Available Colours: silver Type of Installation: Recessed ceiling mounting Dimensions: L 866, B 75, H 2 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 2750lm System power: 21W Beam Angle: 60°/58° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 16,6 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	2750 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	21 W

Mounting mode

Wall recessed

Shape and measurements

Length: 2.95 in
Width: 34.09 in
Height: 1.46 in

Adjustability

Fixed

Electric

System power: 21 W

Protection

IP: 20