Product data sheet

LIGHT LINEAR VT 6 STREET AND AREA LUMINAIRES VT-20023-T3-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K, 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket and clear toughened glass - Maximum wind load resistance is 120 km/h - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	107 W	CRI	80
Total flux	8495 lm	LOR	100%
Luminous efficacy	79 lm/W	Total power	107 W

Mounting mode

Pole integrated

Shape and measurements

Length: 3.54 in Width: 5.91 in Height: 35.24 in Weight: 30.4 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 107 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65 IK: 07

Surface temperature: 40°C