

# Product data sheet


RAY F2 DIFF.METAL. BCO  
F5921009  
FLOS



IP  
20

Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. Resistive dimmer wired on cord for 0-100% light adjustment. Power cord with black PVC/PVC (flat) sheath (1500 mm). Net weight glass diffuser 9.2 kg metal diffuser 6.2 kg.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 230 W   | Socket      | E27     |
| Lamp flux          | 4210 lm | LOR         | 43%     |
| Luminous efficacy  | 8 lm/W  | ULOR        | 15%     |
| CCT                | 2821 K  | Total flux  | 1792 lm |
| CRI                | 99      | Total power | 230 W   |

## Mounting mode

Standing / Bollard, Floor mounted

## Shape and measurements

Length: 22.07 in  
Width: 22.07 in  
Height: 67.09 in

## Adjustability

Fixed

## Electric

System power: 230 W

## Protection

IP: 20