Product data sheet

LUCAS VI (WALL FITTING) 9.832.2032.15


LEIPZIGER LEUCHTEN





High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure sodium vapour lamp | | |
|--------------------------------------|---------|--|
| Nominal lamp power | 70 W | |
| Lamp flux | 5600 lm | |
| Luminous efficacy | 57 lm/W | |
| CCT | 2000 H | |
| CRI | 25 | |

| LOR | 84% |
|-------------|---------|
| Total flux | 4691 lm |
| Total power | 83 W |
| | |
| | |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 83 W

Protection

IP: 55