

Product data sheet


MINI MULTIPLE TRIMLESS 1X GU10
103815XX
MODULAR



IP
20


Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your choice. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours.

Light output 1



1 x Halogen low voltage lamp without reflector

| | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W | Socket | Gu10 |
| Lamp flux | 525 lm | LOR | 91% |
| Luminous efficacy | 10 lm/W | Total flux | 477 lm |
| CCT | 2800 K | Total power | 50 W |
| CRI | 100 | | |



1 x Halogen low voltage lamp without reflector

| | | | |
|--------------------|--------|-------------|--------|
| Nominal lamp power | 50 W | LOR | 87% |
| Lamp flux | 525 lm | Total flux | 457 lm |
| Luminous efficacy | 9 lm/W | Total power | 50 W |
| CCT | 2800 K | | |
| CRI | 100 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.02 in

Width: 4.02 in

Height: 0.39 in

Adjustability

Cardanic

Electric

System power: 50 W

Protection

IP: 20