


Product data sheet

OCULUS LINEAR LED 4551MM
840
BRIGHT SPECIAL LIGHTING




Housing :Extruded aluminium Diffuser :Matt opal cover of extruded PMMA Control Gear :Built-in electronic driver Watt :Max 2x131.2W IP :40 IK :05 • LED replacement with tools

Light output 1



| | | | |
|--------------------|----------|-------------|----------|
| 1 x LED | | | |
| Nominal lamp power | 270.2 W | LOR | 100% |
| Lamp flux | 29792 lm | ULOR | 50% |
| Luminous efficacy | 120 lm/W | Total flux | 29792 lm |
| CCT | 4000 K | Total power | 247.8 W |
| CRI | 84 | | |



| | | | |
|--------------------|----------|-------------|----------|
| 1 x LED | | | |
| Nominal lamp power | 181.1 W | LOR | 100% |
| Lamp flux | 19936 lm | ULOR | 50% |
| Luminous efficacy | 110 lm/W | Total flux | 19936 lm |
| CCT | 4000 K | Total power | 181.1 W |
| CRI | 84 | | |

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 13.07 in
Width: 178.11 in
Height: 2.36 in

Adjustability

Height adjustable

Electric

System power: 181.1-247.8 W
Appliance Class: I

Protection

IP: 40
IK: 05