

# Product data sheet


ARNO I LED  
9.134.9268.01  
LEIPZIGER LEUCHTEN



IP  
66

recom. pole height: 5.00m – 16.00m light standards: medium and high lighting requirements lamp: incl. 2 Z LED modules 8 designed to approved Zhaga standard colour temperature: 3.000K warm white or 4.000K neutral white LED gear: depending on the electronic driver: up to 50.000 to 100.000 hours; PL-CP or HBM: CLO mode LED life expectancy: PL-CP or HBM: up to 50.000 to 60.000 hours/L100 resp. 50.000 hours/L80; SMD: up to 50.000 hours/L70 light control: at extra cost: power reduction, dimming or CLEVER LIGHT 10 optical system: computer-optimised reflector for Zhaga LED modules for directed light and wide spacings light distribution: asymmetrical wide beam luminaire head: die cast aluminium, powder coated colour: DB 703; other colours on request glazing: flat, clear toughened glass glazing, to be hinged down wiring: completely wired; incl. 8.00m cable; other lengths on demand installation: for top entry ø 76mm and ø 60mm, inclination 5° resp. 10° or for side entry ø 60mm; dispatch standard: for top entry, 5° accessory: column- and wall bracket, column, pole accessories – to be ordered separately application areas: residential and local distribution roads, main streets, car parks, factory premises, hotels, holiday parks

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	96 W	CRI	70
Total flux	11350 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	96 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 24.21 in  
Width: 16.73 in  
Height: 5.67 in  
Weight: 13.8 kg

## Adjustability

Height adjustable

## Electric

System power: 96 W

## Protection

IP: 66