


Product data sheet

KAP 105
03.4571.74/HI PAR 51/35W/40°
FLOS



Luminaire with embedded installations on ceilings for halogen lamps, metal halide and LED. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).

Light output 1



1 x Metal halide lamp

| | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 35 W | Socket | Gx10 |
| Lamp flux | 2194 lm | LOR | 33% |
| Luminous efficacy | 63 lm/W | Total flux | 717 lm |
| CCT | 3000 K | Total power | 35 W |
| CRI | 80 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.13 in

Width: 4.13 in

Height: 7.68 in

Adjustability

Fixed

Electric

System power: 35 W

Appliance Class: III

Protection

IP: 20