Product data sheet

LUCAS I (WALL FITTING) 9.835.2056.15

LEIPZIGER LEUCHTEN






CRI

CRI




Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



I x High pressure sodium vapour lamp		
Nominal lamp power	100 W	
Lamp flux	10400 lm	
Luminous efficacy	76 lm/W	
CCT	2000 K	

LOR 84%
Total flux 8713 lm
Total power 115 W



1 x High pressure sodium vapour lamp

J ,			
Nominal lamp power	70 W	LOR	84%
Lamp flux	5600 lm	Total flux	4691 lm
Luminous efficacy	57 lm/W	Total power	83 W
CCT	2000 K		

25

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Design

Material impression: Matt Color of housing: White Electric

System power: 83-115 W

Ballast: ECG

Integrated sensors

25

Integrated sensors: Motion sensor

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F