

Product data sheet


LDSQ6B LED 6" SQUARE RECESSED DOWNLIGHT
LDSQ6B10D010 EU6B10209024 6LBCSSQ1MMS
COOPER LIGHTING



IP
47

Square new construction downlight or lensed wall wash, Excellent light control and low aperture brightness, Designed for standard or shallow plenums; ENERGY STAR® qualified, Square die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, W2N Tunable White 2700K-6500K or 2000K-5000K, Lumens: 1,000-7,000; 0-10V dimming down to 1%, WaveLinx and DLVP connected lighting systems compatibility, Plaster lathing ring accessory offered for flush reflector transition

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.05 W	CRI	100
Total flux	834 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	10.05 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 10.05 W

Protection

IP: 47