


Product data sheet


1M RTW 2-5000PS 24V RGB 2X (5060, 300 LED, LUX)
021400
ARLIGHT RUS LLC




IP
33

Герметичная лента IP67 (силикон, экструзия), светодиоды smd 5060, 60шт/м Белая плата 10мм. Цвет Мультицвет R/G/B. Питание 24V, мощность 14.4 Вт/м (72 Вт на 5м). Угол 120°. Размеры 5000x12x5мм. Мин.отрезок 100мм, 6 светодиодов.


Light output 1




1 x LED			
Nominal lamp power	12.4 W	LOR	100%
Lamp flux	413 lm	Total flux	413 lm
Luminous efficacy	33 lm/W	Total power	124 W
CCT	0 K		
CRI	99		



1 x LED			
Nominal lamp power	4.1 W	LOR	100%
Lamp flux	110 lm	Total flux	110 lm
Luminous efficacy	27 lm/W	Total power	4.1 W
CCT	0 K		
CRI	-29		



1 x LED			
Nominal lamp power	4.1 W	LOR	100%
Lamp flux	46 lm	Total flux	46 lm
Luminous efficacy	11 lm/W	Total power	4.1 W
CCT	0 K		
CRI	-50		



1 x LED

Nominal lamp power	4.2 W	LOR	100%
Lamp flux	257 lm	Total flux	257 lm
Luminous efficacy	61 lm/W	Total power	4.2 W
CCT	0 K		
CRI	-18		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.37 in

Width: 0.47 in

Height: 0.20 in

Adjustability

Fixed

Electric

System power: 4.1-124 W

Protection

IP: 33