

Product data sheet


METROPOLI R7S_STRUCTURE ALU
D20/27.2V
LUCEPLAN




IP
20

Sobrio e impeccabile, il telaio in alluminio pressofuso contiene il diffusore e dispone di una serie di ottiche intercambiabili che permette di utilizzare a scelta lampadine alogene o fluorescenti, Metropoli viene ora proposta con nuove sorgenti LED per una maggiore efficienza luminosa. Il diffusore è in vetro stampato prismaticizzato o policarbonato opalino (tenuta stagna).

Light output 1



1 x Halogen low voltage lamp without reflector			
Nominal lamp power	80 W	Socket	R7S
Lamp flux	1400 lm	LOR	61%
Luminous efficacy	9 lm/W	Total flux	858 lm
CCT	3000 K	Total power	100 W
CRI	99		



1 x Halogen low voltage lamp without reflector			
Nominal lamp power	70 W	Socket	E27
Lamp flux	1200 lm	LOR	61%
Luminous efficacy	7 lm/W	Total flux	736 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.16 in
Width: 10.62 in
Height: 10.57 in

Adjustability

Fixed

Electric

System power: 100 W

Protection

IP: 20